



MSA PROJECT

Seminar on Mining Software Repositories

2010

Imagine



You as Quality Manager

- ▶ 30,000 classes
- ▶ ~ 5.5 million lines of code
- ▶ ~3000 defect per release
- ▶ 700 developers

Your product

Your Boss

Test the system!
You have 6 months!
And don't miss a bug!





Your Testers



The Problem

- ▶ Not enough **time** to test everything
 - ▶ What to test? What to test first?
- ▶ Not enough **money** to pay enough testers
 - ▶ To which extend?

Where are the most defect prone entities in my system?

Can we learn from history?




Your Task


- ▶ Map bug reports to code changes (transactions)
 - ▶ Which code change introduced which bug?
- ▶ Map bug reports to files
 - ▶ How many defects have been fixed per source code file?

Predicting Defects for Eclipse


by Zimmermann et al. (Session 3)



Your Task



Your Task (2)



Your Input

- ▶ Project: JEdit
 - ▶ Programmer's text editor
 - ▶ Sourceforge project: <http://sourceforge.net/projects/jedit/>
- ▶ We will provide you with
 - ▶ Bug reports (XHTML files)
 - ▶ Tarball containing SVN (Subversion) mirror
- ▶ Download from Webpage
 - ▶ http://www.st.cs.uni-saarland.de/edu/msa10/jedit_reports.tar.gz
 - ▶ http://www.st.cs.uni-saarland.de/edu/msa10/svn_repo_14_01_2010.tar.gz



Bug Reports

sourceforge FIND AND DEVELOP OPEN SOURCE SOFTWARE Welcome, Guest! [Log in](#) | [Create Account](#)

[Find Software](#) | [Develop](#) | [Create Project](#) | [Blog](#) | [Site Support](#) | [About](#) [Search](#)

SourceForge.net > [Projects](#) > [jEdit](#) > [Tracker](#) > [Bugs](#) > View

jEdit

[Share](#) [Donate](#)

[Summary](#) | [Files](#) | **[Support](#)** | [Develop](#) | [Hosted Apps](#) | **Tracker** | [Mailing Lists](#) | [Code](#)

[Add new](#) [Browse](#)

Tracker: [Bugs](#) Monitor

5 Can't disable "Restore previously open files on startup" - ID: 2920352 Last Update: Comment added ([shlomy](#))

Details: Although I have unchecked "Restore previously open files on startup" in Global Options, and the setting appears to be saved (it's still unchecked when I restart jEdit), it still always reloads previously open files on startup anyway.

Using jEdit 4.3, Java 1.6.0_17, Windows XP SP3.

Submitted: Eric Rosenberger (twofitysix) - 2009-12-23 22:30:09 UTC	Assigned: Shlomy Reinstein
Priority: 5	Category: None
Status: Closed	Group: None
Resolution: Fixed	Visibility: Public

Comments (8)

Date: 2009-12-25 17:24:52 UTC
Sender: [shlomy](#)
Fixed in SVN revision 16731.

Date: 2009-12-24 05:12:20 UTC
Sender: [ezust](#)
if no files are restored on startup then there should be only an untitled buffer, which should be in the same directory as that specified by global options - file system browser - general - default path.

Date: 2009-12-24 05:09:04 UTC
Sender: [ezust](#)
yes, reproduced with -noplugins. It only restores the active open file, none of the others.



Bug Reports

XHTML



```
<div id="comment_table_container">
  <table class="comments"><thead></thead><tfoot></tfoot><tbody><tr class="artifact_comment" id="artifact_comment_3445446"><td colspan="1" r
  >>> <div class="yui-gf">
  >>>> <div class="yui-u first">
  >>>>> <input type="hidden" name="artifact_comment_3445446_adddate" value="1233353501"></input>
  >>>>> <p>
  >>>>>> Date: 2009-01-30 22:11<br clear="none"></br>
  >>>>>> Sender: <a shape="rect" href="/user/k_satoda/" title="Kazutoshi Satoda">k_satoda</a><a shape="rect" href="/help/icon_legend.php?co
  >>>>>> </p>
  >>>>> </div>
  >>>> <div class="yui-u">
  >>>>>>>>>> <p>Fixed in r14534.<br clear="none"></br>
  <br clear="none"></br>
  I didn't know the way to remove lines from a visible line to an<br clear="none"></br>
  invisible line. Thanks.<br clear="none"></br>
  <br clear="none"></br>
  <br clear="none"></br>
  </p>
  >>>>> </div>
```



- ▶ Hint: One transaction can fix more than one bug!



SVN tarball

```
pearl:~ kim$ svn info file:///Users/kim/Documents/Teaching/msa2010/project/svn_repo_14_01_2010/  
Path: svn_repo_14_01_2010  
URL: file:///Users/kim/Documents/Teaching/msa2010/project/svn_repo_14_01_2010  
Repository Root: file:///Users/kim/Documents/Teaching/msa2010/project/svn_repo_14_01_2010  
Repository UUID: 25ceb265-6a78-4dce-b758-64b437aadf78  
Revision: 16942  
Node Kind: directory  
Last Changed Author: ezust  
Last Changed Rev: 16942  
Last Changed Date: 2010-01-17 06:05:58 +0100 (Sun, 17 Jan 2010)
```

- ▶ To parse log you can use:
 - ▶ `svn log --xml`

- ▶ or use any SVN library

Programming Language

We don't care!

But: It has to run on CIP pool computers!

Hand In

- ▶ A CSV file containing pairs `<transaction_id, bug_id>`
 - ▶ Which bug was fixed in which transaction?
- ▶ A CSV file containing pairs `<svn_path, #bugs>`
 - ▶ How many bugs could be mapped to file.
- ▶ Executable program or script (CIP-pool)
- ▶ Documentation
 - ▶ How to reproduce the provided files?
 - ▶ How did you manage the mappings? (heuristics)
 - ▶ Why is your program/script good, where could it be improved?





Questions